


配光特性

図番 MR150880





カタログ番号	X164CW		
オプション番号	3500K Ra95		
使用ランプ	XTM19953513CCA		
ランプ光束	1300.0	lm	1.000
最大光度	969	cd	
1/2ビーム角			
A断面	71.00 °		
C断面			
B断面			

角度	光度
0°	969
10°	947
20°	821
30°	626
40°	323
50°	66
60°	20
70°	11
80°	4
90°	0
100°	0
110°	0
120°	0
130°	0
140°	0
150°	0
160°	0
170°	0
180°	0



断面



照明率表		平均照度=台数*照明率*保守率*1300(光束)/(間口*奥行)											
床面反射率(%)		20											
天井面反射率(%)		80			60			40			20		
壁面反射率(%)		50	30	10	50	30	10	50	30	10	50	30	10
室	0.50	0.52	0.46	0.42	0.51	0.46	0.42	0.50	0.45	0.42	0.50	0.45	0.42
	0.70	0.64	0.58	0.54	0.63	0.58	0.54	0.62	0.57	0.54	0.61	0.56	0.53
	1.00	0.75	0.69	0.65	0.73	0.68	0.65	0.71	0.67	0.64	0.70	0.66	0.64
	1.25	0.80	0.75	0.71	0.78	0.74	0.70	0.76	0.72	0.69	0.74	0.71	0.69
	1.50	0.84	0.79	0.76	0.82	0.78	0.74	0.80	0.76	0.73	0.78	0.75	0.72
指	2.00	0.89	0.85	0.82	0.86	0.83	0.80	0.84	0.81	0.79	0.82	0.79	0.77
	2.50	0.92	0.89	0.86	0.89	0.86	0.84	0.87	0.84	0.82	0.84	0.82	0.80
	3.00	0.94	0.91	0.88	0.91	0.88	0.86	0.88	0.86	0.84	0.85	0.83	0.82
	4.00	0.98	0.95	0.92	0.94	0.92	0.90	0.91	0.89	0.87	0.88	0.86	0.85
	5.00	0.99	0.97	0.95	0.96	0.94	0.92	0.92	0.91	0.89	0.89	0.88	0.87
数	7.00	1.01	1.00	0.98	0.97	0.96	0.95	0.94	0.93	0.91	0.90	0.89	0.89
	10.00	1.03	1.02	1.01	0.99	0.98	0.97	0.95	0.94	0.93	0.91	0.91	0.90