



配光特性

図番 YL230208



カタログ番号	K4617(B・W) 3000K Ra80
使用ランプ	LED 1.9W
器具光束	164.0 lm _{1,000}
下方効率	100.0 %
上方効率	0.0 %
最大取付間隔	
A断面	0.34 H
C断面	
B断面	

	角度	光度
	0°	928
	10°	464
	20°	125
	30°	14
	40°	2
	50°	0
	60°	0
	70°	0
	80°	0
	90°	0
	100°	0
	110°	0
	120°	0
	130°	0
	140°	0
	150°	0
	160°	0
170°	0	
180°	0	



照明率表		平均照度=台数×照明率×保守率×164(光束)/(間口×奥行)												
床面反射率 (%)		20												
天井面反射率 (%)		80			60			40			20			0
壁面反射率 (%)		50	30	10	50	30	10	50	30	10	50	30	10	0
室	0.50	0.88	0.85	0.83	0.88	0.84	0.82	0.87	0.84	0.82	0.86	0.84	0.82	0.81
	0.70	0.95	0.91	0.89	0.94	0.90	0.88	0.93	0.90	0.88	0.92	0.89	0.87	0.86
	1.00	1.00	0.97	0.94	0.99	0.96	0.93	0.97	0.95	0.93	0.96	0.94	0.92	0.91
	1.25	1.03	1.00	0.97	1.01	0.99	0.96	0.99	0.97	0.95	0.98	0.96	0.94	0.93
	1.50	1.06	1.02	1.00	1.03	1.01	0.98	1.01	0.99	0.97	0.99	0.97	0.96	0.94
指	2.00	1.09	1.06	1.03	1.06	1.03	1.01	1.03	1.01	1.00	1.01	0.99	0.98	0.96
	2.50	1.10	1.08	1.06	1.07	1.05	1.03	1.04	1.03	1.01	1.02	1.00	0.99	0.97
	3.00	1.12	1.09	1.07	1.08	1.06	1.05	1.05	1.04	1.02	1.02	1.01	1.00	0.97
	4.00	1.14	1.12	1.10	1.10	1.08	1.07	1.06	1.05	1.04	1.03	1.02	1.01	0.98
	5.00	1.15	1.13	1.12	1.11	1.09	1.08	1.07	1.06	1.05	1.03	1.03	1.02	0.99
数	7.00	1.16	1.15	1.14	1.12	1.11	1.10	1.08	1.07	1.06	1.04	1.03	1.03	0.99
	10.00	1.17	1.16	1.16	1.13	1.12	1.11	1.08	1.08	1.07	1.04	1.04	1.04	1.00