







カタログ番号	618EGGBOARD M3103W91	
使用ランプ	LED 32.1W	
ランプ光束	3328.0	lm <small>1,000</small>
器具効率	100.3 %	
下方効率	39.7 %	
上方効率	60.5 %	
最大取付間隔	下方向	上方向
A断面		
C断面		
B断面		

角度	光度
0°	1197
10°	1323
20°	1320
30°	832
40°	266
50°	51
60°	4
70°	1
80°	0
90°	5
100°	61
110°	141
120°	249
130°	385
140°	539
150°	687
160°	803
170°	874
180°	898

Eggboard matrix 800X800

照明率表		平均照度=台数 * 照明率 * 保守率 * 3328 (光束) / (間口 * 奥行)												
床面反射率(%)		20												
天井面反射率(%)		80			60			40			20			0
壁面反射率(%)		50	30	10	50	30	10	50	30	10	50	30	10	0
室	0.50	0.43	0.36	0.32	0.38	0.33	0.29	0.33	0.29	0.27	0.28	0.26	0.24	0.21
	0.70	0.53	0.47	0.42	0.47	0.42	0.38	0.40	0.37	0.34	0.34	0.32	0.30	0.25
	1.00	0.64	0.58	0.53	0.55	0.50	0.47	0.47	0.44	0.41	0.39	0.37	0.35	0.29
	1.25	0.70	0.64	0.59	0.60	0.56	0.52	0.51	0.47	0.45	0.42	0.40	0.38	0.31
	1.50	0.75	0.69	0.64	0.64	0.59	0.56	0.53	0.50	0.48	0.44	0.42	0.40	0.33
指	2.00	0.81	0.76	0.71	0.68	0.65	0.61	0.57	0.54	0.52	0.46	0.44	0.43	0.34
	2.50	0.85	0.80	0.76	0.71	0.68	0.65	0.59	0.57	0.55	0.47	0.46	0.45	0.35
	3.00	0.88	0.83	0.80	0.73	0.71	0.68	0.60	0.58	0.57	0.48	0.47	0.46	0.36
	4.00	0.92	0.88	0.85	0.76	0.74	0.72	0.63	0.61	0.60	0.50	0.49	0.48	0.37
数	5.00	0.94	0.91	0.88	0.78	0.76	0.74	0.64	0.62	0.61	0.51	0.50	0.49	0.37
	7.00	0.97	0.94	0.92	0.80	0.79	0.77	0.65	0.64	0.63	0.51	0.51	0.50	0.38
	10.00	0.99	0.97	0.96	0.82	0.81	0.80	0.66	0.66	0.65	0.52	0.52	0.51	0.39