




配光特性

図番 8073_14



カタログ番号	708TM03/8073/14/DA		
使用ランプ	LED24W		
ランプ光束	1872.0	lm	1.000
最大光度	17363.9 cd		
1/2ビーム角			
A断面	16.00 °		
C断面			
B断面			

	角度	光度
	0°	17364
	10°	5980
	20°	1119
	30°	14
	40°	4
	50°	2
	60°	2
	70°	1
	80°	1
	90°	1
	100°	0
	110°	0
	120°	0
	130°	0
	140°	0
	150°	0
	160°	0
170°	0	
180°	0	



照明率表		平均照度=台数 * 照明率 * 保守率 * 1872 (光束) / (間口 * 奥行)											
床面反射率 (%)		20											
天井面反射率 (%)		80			60			40			20		
壁面反射率 (%)		50	30	10	50	30	10	50	30	10	50	30	10
室	0.50	0.97	0.94	0.92	0.96	0.93	0.92	0.95	0.93	0.92	0.95	0.93	0.91
	0.70	1.01	0.98	0.96	1.00	0.97	0.95	0.99	0.97	0.95	0.98	0.96	0.95
	1.00	1.05	1.02	1.00	1.03	1.01	0.99	1.02	1.00	0.98	1.01	0.99	0.97
	1.25	1.07	1.04	1.02	1.05	1.03	1.01	1.03	1.01	1.00	1.02	1.00	0.99
	1.50	1.09	1.06	1.04	1.07	1.04	1.02	1.04	1.03	1.01	1.03	1.01	1.00
指	2.00	1.11	1.09	1.07	1.08	1.06	1.05	1.06	1.04	1.03	1.03	1.02	1.01
	2.50	1.13	1.11	1.09	1.10	1.08	1.06	1.07	1.05	1.04	1.04	1.03	1.02
	3.00	1.14	1.12	1.10	1.11	1.09	1.07	1.07	1.06	1.05	1.04	1.03	1.03
	4.00	1.16	1.14	1.12	1.12	1.10	1.09	1.08	1.07	1.06	1.05	1.04	1.03
	5.00	1.17	1.15	1.14	1.13	1.11	1.10	1.09	1.08	1.07	1.05	1.04	1.04
数	7.00	1.18	1.17	1.16	1.13	1.13	1.12	1.09	1.09	1.08	1.05	1.05	1.05
	10.00	1.19	1.18	1.17	1.14	1.13	1.13	1.10	1.09	1.09	1.06	1.05	1.05