





カタログ番号	T533B(B・W)
使用ランプ	
器具光束	1498.0 lm _{1.000}
最大光度	3393.6 cd
1 / 2 ビーム角	
A 断面	36.00°
C 断面	
B 断面	

	角度	光度
	0°	3394
	10°	2786
	20°	1378
	30°	410
	40°	105
	50°	35
	60°	24
	70°	19
	80°	15
	90°	13
	100°	0
	110°	0
	120°	0
	130°	0
	140°	0
	150°	0
	160°	0
170°	0	
180°	0	



照明率表		平均照度=台数*照明率*保守率* 1498 (光束)/(間口*奥行)												
床面反射率 %		20												
天井面反射率 %		80			60			40			20			0
壁面反射率 %		50	30	10	50	30	10	50	30	10	50	30	10	0
室	0.50	0.73	0.68	0.65	0.72	0.68	0.65	0.72	0.68	0.65	0.71	0.67	0.65	0.63
	0.70	0.82	0.77	0.74	0.81	0.77	0.74	0.80	0.76	0.73	0.79	0.75	0.73	0.71
	1.00	0.91	0.86	0.82	0.89	0.85	0.82	0.87	0.84	0.81	0.86	0.83	0.80	0.79
	1.25	0.95	0.90	0.87	0.93	0.89	0.86	0.91	0.88	0.85	0.89	0.86	0.84	0.82
	1.50	0.98	0.94	0.90	0.96	0.92	0.89	0.93	0.90	0.88	0.91	0.89	0.87	0.85
指	2.00	1.02	0.98	0.95	0.99	0.96	0.93	0.97	0.94	0.92	0.94	0.92	0.90	0.88
	2.50	1.05	1.02	0.99	1.02	0.99	0.96	0.99	0.96	0.94	0.96	0.94	0.92	0.90
	3.00	1.07	1.04	1.01	1.03	1.01	0.99	1.00	0.98	0.96	0.97	0.95	0.94	0.91
	4.00	1.10	1.07	1.05	1.06	1.04	1.02	1.02	1.00	0.99	0.99	0.97	0.96	0.93
数	5.00	1.11	1.09	1.07	1.07	1.05	1.04	1.03	1.02	1.00	1.00	0.99	0.97	0.94
	7.00	1.13	1.12	1.10	1.09	1.07	1.06	1.05	1.03	1.02	1.01	1.00	0.99	0.96
	10.00	1.15	1.14	1.12	1.10	1.09	1.08	1.06	1.05	1.04	1.02	1.01	1.00	0.97