



# 配光特性

図番 YL220015



カタログ番号	K4637(B・W)	
使用ランプ		
器具光束	573.0 lm <sub>1,000</sub>	
器具効率	100.0 %	
下方効率	50.0 %	
上方効率	50.0 %	
最大取付間隔	下方向	上方向
A断面		
C断面		
B断面		

	角度	光度
	0°	99
	10°	98
	20°	93
	30°	85
	40°	74
	50°	61
	60°	45
	70°	28
	80°	10
	90°	0
	100°	10
	110°	28
	120°	45
	130°	61
	140°	74
	150°	85
	160°	93
170°	98	
180°	99	



照明率表		平均照度=台数×照明率×保守率×573(光束)/(間口×奥行)											
床面反射率 (%)		20											
天井面反射率 (%)		80			60			40			20		
壁面反射率 (%)		50	30	10	50	30	10	50	30	10	50	30	10
室	0.50	0.33	0.26	0.21	0.29	0.23	0.19	0.25	0.20	0.17	0.21	0.17	0.14
	0.70	0.44	0.36	0.31	0.38	0.32	0.27	0.33	0.28	0.24	0.27	0.23	0.21
	1.00	0.57	0.49	0.43	0.49	0.42	0.38	0.41	0.37	0.33	0.35	0.31	0.28
	1.25	0.64	0.56	0.50	0.55	0.49	0.44	0.46	0.42	0.38	0.39	0.35	0.33
	1.50	0.69	0.62	0.56	0.59	0.54	0.49	0.50	0.46	0.43	0.42	0.39	0.36
指	2.00	0.77	0.70	0.65	0.66	0.61	0.57	0.56	0.52	0.49	0.46	0.44	0.41
	2.50	0.82	0.76	0.71	0.70	0.66	0.62	0.59	0.56	0.53	0.49	0.47	0.45
	3.00	0.86	0.80	0.76	0.73	0.69	0.66	0.62	0.59	0.56	0.51	0.49	0.47
	4.00	0.91	0.86	0.82	0.77	0.74	0.71	0.65	0.63	0.61	0.54	0.52	0.51
	5.00	0.94	0.90	0.86	0.80	0.77	0.74	0.67	0.65	0.63	0.55	0.54	0.53
数	7.00	0.97	0.94	0.92	0.83	0.81	0.79	0.70	0.68	0.67	0.57	0.56	0.55
	10.00	1.00	0.98	0.96	0.85	0.84	0.82	0.71	0.70	0.69	0.59	0.58	0.57