






カタログ番号	T4519B
使用ランプ	LED 21W
器具光束	2170.0 lm <small>1.000</small>
最大光度	1168.3 cd
1 / 2 ビーム角	
A 断面	
C 断面	
B 断面	

	角度	光度
	0°	1168
	10°	1178
	20°	1091
	30°	823
	40°	563
	50°	199
	60°	43
	70°	15
	80°	5
	90°	0
	100°	0
	110°	0
	120°	0
	130°	0
	140°	0
	150°	0
	160°	0
170°	0	
180°	0	



照明率表		平均照度=台数*照明率*保守率* 2170 (光束)/(間口*奥行)												
床面反射率 %		20												
天井面反射率 %		80			60			40			20			0
壁面反射率 %		50	30	10	50	30	10	50	30	10	50	30	10	0
室	0.50	0.49	0.41	0.37	0.48	0.41	0.37	0.47	0.41	0.37	0.46	0.40	0.36	0.35
	0.70	0.63	0.55	0.50	0.61	0.55	0.50	0.60	0.54	0.50	0.59	0.53	0.49	0.47
	1.00	0.76	0.69	0.64	0.74	0.68	0.64	0.72	0.67	0.63	0.71	0.66	0.62	0.60
	1.25	0.84	0.77	0.72	0.81	0.75	0.71	0.79	0.74	0.70	0.77	0.73	0.69	0.67
	1.50	0.89	0.83	0.78	0.86	0.81	0.77	0.84	0.79	0.75	0.81	0.77	0.74	0.72
指	2.00	0.95	0.90	0.86	0.92	0.88	0.84	0.89	0.86	0.82	0.87	0.84	0.81	0.78
	2.50	1.00	0.95	0.91	0.96	0.92	0.89	0.93	0.90	0.87	0.90	0.87	0.85	0.82
	3.00	1.03	0.98	0.95	0.99	0.95	0.92	0.95	0.92	0.90	0.92	0.90	0.88	0.85
	4.00	1.07	1.03	1.00	1.03	1.00	0.97	0.99	0.96	0.94	0.95	0.94	0.92	0.89
	5.00	1.09	1.06	1.03	1.05	1.02	1.00	1.01	0.99	0.97	0.97	0.96	0.94	0.91
数	7.00	1.12	1.09	1.07	1.07	1.05	1.04	1.03	1.02	1.00	0.99	0.98	0.97	0.93
	10.00	1.14	1.12	1.11	1.09	1.08	1.07	1.05	1.04	1.03	1.01	1.00	0.99	0.95