



配光特性

図番 YL210284



カタログ番号	J565CN		
使用ランプ			
器具光束	1211.0	lm	1.000
最大光度	6181.8	cd	
1 / 2 ビーム角			
A 断面	19.00°		
C 断面			
B 断面			

	角度	光度
	0°	6182
	10°	2921
	20°	989
	30°	90
	40°	26
	50°	24
	60°	24
	70°	23
	80°	21
	90°	18
	100°	0
	110°	0
	120°	0
	130°	0
	140°	0
	150°	0
	160°	0
170°	0	
180°	0	



照明率表		平均照度=台数*照明率*保守率* 1211 (光束)/(間口*奥行)												
床面反射率 %		20												0
天井面反射率 %		80			60			40			20			0
壁面反射率 %		50	30	10	50	30	10	50	30	10	50	30	10	0
室	0.50	0.82	0.78	0.75	0.81	0.77	0.75	0.80	0.77	0.75	0.80	0.77	0.74	0.73
	0.70	0.88	0.84	0.81	0.87	0.83	0.81	0.86	0.83	0.80	0.85	0.82	0.80	0.79
	1.00	0.95	0.90	0.87	0.93	0.89	0.86	0.91	0.88	0.86	0.90	0.87	0.85	0.83
	1.25	0.98	0.94	0.91	0.96	0.92	0.90	0.94	0.91	0.89	0.92	0.90	0.88	0.86
	1.50	1.01	0.97	0.94	0.98	0.95	0.92	0.96	0.93	0.91	0.94	0.92	0.90	0.88
指	2.00	1.04	1.01	0.98	1.01	0.98	0.96	0.99	0.96	0.94	0.96	0.94	0.92	0.90
	2.50	1.07	1.03	1.01	1.03	1.01	0.98	1.00	0.98	0.96	0.97	0.96	0.94	0.91
	3.00	1.09	1.05	1.03	1.05	1.02	1.00	1.02	0.99	0.98	0.98	0.97	0.95	0.93
	4.00	1.11	1.08	1.06	1.07	1.05	1.03	1.03	1.01	1.00	1.00	0.98	0.97	0.94
	5.00	1.13	1.10	1.08	1.08	1.06	1.05	1.04	1.03	1.01	1.01	0.99	0.98	0.95
数	7.00	1.14	1.13	1.11	1.10	1.08	1.07	1.06	1.04	1.03	1.02	1.01	1.00	0.96
	10.00	1.16	1.15	1.13	1.11	1.10	1.09	1.07	1.06	1.05	1.02	1.02	1.01	0.97