



配光特性

図番 YL210295



カタログ番号	J571BN
使用ランプ	
器具光束	1378.0 lm <small>1.000</small>
最大光度	16830.9 cd
1 / 2 ビーム角	
A 断面	15.00°
C 断面	
B 断面	

	角度	光度
	0°	16831
	10°	4374
	20°	226
	30°	52
	40°	24
	50°	21
	60°	20
	70°	14
	80°	12
	90°	11
	100°	0
	110°	0
	120°	0
	130°	0
	140°	0
	150°	0
	160°	0
170°	0	
180°	0	



照明率表		平均照度=台数*照明率*保守率* 1378 (光束)/(間口*奥行)											
床面反射率 %		20											
天井面反射率 %		80			60			40			20		
壁面反射率 %		50	30	10	50	30	10	50	30	10	50	30	10
室	0.50	0.96	0.93	0.92	0.96	0.93	0.91	0.95	0.93	0.91	0.95	0.92	0.91
	0.70	1.00	0.97	0.94	0.99	0.96	0.94	0.98	0.95	0.94	0.97	0.95	0.93
	1.00	1.03	1.00	0.98	1.02	0.99	0.97	1.00	0.98	0.96	0.99	0.97	0.95
	1.25	1.06	1.02	1.00	1.04	1.01	0.99	1.02	0.99	0.98	1.00	0.98	0.97
	1.50	1.07	1.04	1.02	1.05	1.02	1.00	1.03	1.01	0.99	1.01	0.99	0.98
指	2.00	1.10	1.07	1.05	1.07	1.05	1.03	1.04	1.02	1.01	1.02	1.00	0.99
	2.50	1.12	1.09	1.07	1.08	1.06	1.04	1.05	1.04	1.02	1.02	1.01	1.00
	3.00	1.13	1.10	1.08	1.09	1.07	1.06	1.06	1.04	1.03	1.03	1.02	1.01
	4.00	1.15	1.13	1.11	1.11	1.09	1.08	1.07	1.06	1.05	1.04	1.03	1.02
	5.00	1.16	1.14	1.12	1.11	1.10	1.09	1.08	1.06	1.06	1.04	1.03	1.02
数	7.00	1.17	1.16	1.14	1.13	1.11	1.10	1.08	1.08	1.07	1.04	1.04	1.03
	10.00	1.18	1.17	1.16	1.13	1.13	1.12	1.09	1.08	1.08	1.05	1.04	1.04