



配光特性

図番 YL220041



カタログ番号	J584DN
使用ランプ	
器具光束	1447.0 lm <small>1.000</small>
最大光度	5750.2 cd
1 / 2 ビーム角	
A 断面	26.00°
C 断面	
B 断面	

	角度	光度
	0°	5750
	10°	3802
	20°	1129
	30°	185
	40°	40
	50°	23
	60°	20
	70°	15
	80°	15
	90°	15
	100°	0
	110°	0
	120°	0
	130°	0
	140°	0
	150°	0
	160°	0
170°	0	
180°	0	



照明率表		平均照度=台数*照明率*保守率* 1447 (光束)/(間口*奥行)												
床面反射率 %		20												0
天井面反射率 %		80			60			40			20			0
壁面反射率 %		50	30	10	50	30	10	50	30	10	50	30	10	0
室	0.50	0.83	0.79	0.76	0.82	0.78	0.76	0.81	0.78	0.76	0.81	0.78	0.75	0.74
	0.70	0.90	0.85	0.83	0.89	0.85	0.82	0.87	0.84	0.82	0.86	0.84	0.81	0.80
	1.00	0.96	0.92	0.89	0.94	0.91	0.88	0.93	0.90	0.87	0.91	0.89	0.87	0.85
	1.25	1.00	0.96	0.92	0.97	0.94	0.91	0.95	0.93	0.90	0.94	0.91	0.89	0.88
	1.50	1.02	0.98	0.95	1.00	0.96	0.94	0.97	0.95	0.92	0.95	0.93	0.91	0.89
指	2.00	1.06	1.02	0.99	1.03	1.00	0.97	1.00	0.98	0.96	0.97	0.95	0.94	0.92
	2.50	1.08	1.05	1.02	1.05	1.02	1.00	1.01	0.99	0.98	0.99	0.97	0.96	0.93
	3.00	1.10	1.07	1.04	1.06	1.04	1.02	1.03	1.01	0.99	0.99	0.98	0.97	0.94
	4.00	1.12	1.09	1.07	1.08	1.06	1.04	1.04	1.03	1.01	1.01	0.99	0.98	0.95
	5.00	1.13	1.11	1.09	1.09	1.07	1.06	1.05	1.04	1.03	1.01	1.00	0.99	0.96
数	7.00	1.15	1.13	1.12	1.10	1.09	1.08	1.06	1.05	1.04	1.02	1.02	1.01	0.97
	10.00	1.16	1.15	1.14	1.12	1.11	1.10	1.07	1.06	1.06	1.03	1.02	1.02	0.98