



配光特性

図番 YL210028



カタログ番号	J602AN
使用ランプ	
器具光束	1754.0 lm <small>1.000</small>
器具効率	100.0 %
下方効率	100.0 %
上方効率	0.0 %
最大取付間隔	
A断面	0.82 H
C断面	
B断面	

	角度	光度
	0°	2767
	10°	2648
	20°	2127
	30°	538
	40°	62
	50°	22
	60°	17
	70°	15
	80°	12
	90°	11
	100°	0
	110°	0
	120°	0
	130°	0
	140°	0
	150°	0
	160°	0
170°	0	
180°	0	



照明率表		平均照度=台数×照明率×保守率×1754(光束)/(間口×奥行)												
床面反射率 (%)		20												
天井面反射率 (%)		80			60			40			20			
壁面反射率 (%)		50	30	10	50	30	10	50	30	10	50	30	10	
室	0.50	0.72	0.67	0.63	0.71	0.66	0.63	0.70	0.66	0.63	0.69	0.66	0.63	
	0.70	0.82	0.77	0.73	0.81	0.76	0.73	0.79	0.76	0.73	0.78	0.75	0.72	
	1.00	0.91	0.86	0.82	0.89	0.85	0.82	0.87	0.84	0.81	0.86	0.83	0.80	
	1.25	0.95	0.91	0.87	0.93	0.89	0.86	0.91	0.88	0.85	0.89	0.86	0.84	
	1.50	0.98	0.94	0.91	0.96	0.92	0.89	0.94	0.91	0.88	0.92	0.89	0.87	
	指	2.00	1.03	0.99	0.96	1.00	0.97	0.94	0.97	0.94	0.92	0.94	0.92	0.90
		2.50	1.05	1.02	0.99	1.02	0.99	0.97	0.99	0.97	0.95	0.96	0.94	0.93
		3.00	1.07	1.04	1.02	1.04	1.01	0.99	1.00	0.98	0.97	0.97	0.96	0.94
		4.00	1.10	1.07	1.05	1.06	1.04	1.02	1.02	1.01	0.99	0.99	0.98	0.97
	数	5.00	1.12	1.09	1.07	1.07	1.06	1.04	1.04	1.02	1.01	1.00	0.99	0.98
7.00		1.14	1.12	1.10	1.09	1.08	1.06	1.05	1.04	1.03	1.01	1.00	0.99	
10.00		1.15	1.14	1.13	1.10	1.09	1.08	1.06	1.05	1.04	1.02	1.01	0.97	