




配光特性

図番 YL230084



カタログ番号	T4551B		
使用ランプ	511 lm		
ランプ光束	511.0	lm	1.000
最大光度	16181.8	cd	
1 / 2 ビーム角			
A 断面	8.00 °		
C 断面			
B 断面			

	角度	光度
	0°	16182
	10°	908
	20°	81
	30°	25
	40°	2
	50°	0
	60°	0
	70°	0
	80°	0
	90°	0
	100°	0
	110°	0
	120°	0
	130°	0
	140°	0
150°	0	
160°	0	
170°	0	
180°	0	



床面反射率 %	20												0	
天井面反射率 %	80			60			40			20			0	
壁面反射率 %	50	30	10	50	30	10	50	30	10	50	30	10	0	
室	0.50	1.03	1.01	0.99	1.02	1.00	0.99	1.02	1.00	0.99	1.01	1.00	0.98	0.98
	0.70	1.06	1.03	1.01	1.05	1.03	1.01	1.04	1.02	1.00	1.03	1.01	1.00	0.99
	1.00	1.09	1.06	1.04	1.07	1.05	1.03	1.06	1.04	1.02	1.04	1.03	1.02	1.00
	1.25	1.10	1.08	1.06	1.08	1.06	1.05	1.07	1.05	1.03	1.05	1.03	1.02	1.01
	1.50	1.12	1.09	1.07	1.09	1.07	1.06	1.07	1.06	1.04	1.05	1.04	1.03	1.01
指	2.00	1.14	1.11	1.09	1.11	1.09	1.07	1.08	1.07	1.06	1.06	1.05	1.04	1.02
	2.50	1.15	1.13	1.11	1.12	1.10	1.09	1.09	1.08	1.06	1.06	1.05	1.04	1.02
	3.00	1.16	1.14	1.12	1.12	1.11	1.10	1.09	1.08	1.07	1.06	1.05	1.05	1.02
	4.00	1.17	1.16	1.14	1.13	1.12	1.11	1.10	1.09	1.08	1.07	1.06	1.05	1.02
数	5.00	1.18	1.17	1.16	1.14	1.13	1.12	1.10	1.09	1.09	1.07	1.06	1.06	1.02
	7.00	1.19	1.18	1.17	1.15	1.14	1.13	1.11	1.10	1.10	1.07	1.06	1.06	1.03
	10.00	1.20	1.19	1.19	1.15	1.15	1.14	1.11	1.11	1.10	1.07	1.07	1.06	1.03

