



# 配光特性

図番 YL230025



カタログ番号	T1165(B・S)		
使用ランプ			
器具光束	518.0	lm	1,000
最大光度	9950.8	cd	
1 / 2 ビーム角			
A 断面	10.00 °		
C 断面			
B 断面			

	角度	光度
	0°	9951
	10°	980
	20°	115
	30°	65
	40°	16
	50°	20
	60°	9
	70°	6
	80°	6
	90°	5
	100°	0
	110°	0
	120°	0
	130°	0
	140°	0
	150°	0
	160°	0
170°	0	
180°	0	



照明率表		平均照度=台数*照明率*保守率* 518 (光束)/(間口*奥行)												
床面反射率 %		20												
天井面反射率 %		80			60			40			20			0
壁面反射率 %		50	30	10	50	30	10	50	30	10	50	30	10	0
室	0.50	0.92	0.89	0.87	0.92	0.89	0.87	0.91	0.88	0.86	0.90	0.88	0.86	0.85
	0.70	0.97	0.93	0.91	0.96	0.93	0.90	0.95	0.92	0.90	0.94	0.91	0.89	0.88
	1.00	1.01	0.98	0.95	1.00	0.97	0.94	0.98	0.96	0.93	0.97	0.94	0.93	0.91
	1.25	1.04	1.01	0.98	1.02	0.99	0.97	1.00	0.98	0.96	0.98	0.96	0.94	0.93
	1.50	1.06	1.03	1.00	1.04	1.01	0.99	1.02	0.99	0.97	0.99	0.97	0.96	0.94
指	2.00	1.09	1.06	1.03	1.06	1.04	1.01	1.04	1.01	1.00	1.01	0.99	0.98	0.96
	2.50	1.11	1.08	1.06	1.08	1.06	1.03	1.05	1.03	1.01	1.02	1.00	0.99	0.97
	3.00	1.13	1.10	1.08	1.09	1.07	1.05	1.06	1.04	1.02	1.03	1.01	1.00	0.97
	4.00	1.15	1.12	1.10	1.11	1.09	1.07	1.07	1.06	1.04	1.04	1.02	1.01	0.98
	5.00	1.16	1.14	1.12	1.12	1.10	1.09	1.08	1.07	1.05	1.04	1.03	1.02	0.99
数	7.00	1.18	1.16	1.15	1.13	1.12	1.11	1.09	1.08	1.07	1.05	1.04	1.03	1.00
	10.00	1.19	1.18	1.17	1.14	1.13	1.12	1.10	1.09	1.08	1.05	1.05	1.04	1.01